

Roto Lo-Boy & Washroom Truck



Item#	Description	Capacity CU.FT.	Truck OD L-W-H	Unit Wt. (Lbs.)	Caster Size	Assembly Ht.
45LB12	RLB	15	47"-28"-20"	60	3"	24"
45RW14*	RWT	23	48"-27"-26"	80	5"	33"

* Sump w/drain holes

- Top Flange for additional strength
- Non-Marking Wheels
- Nominal Wall Thickness .225



Roto & Super Flare Trucks

Item#	Description	Capacity CU.FT.	Truck OD L-W-H	Unit Wt. (Lbs.)	Caster Size	Assembly Ht.
45RF30	Roto-RFT	38	62"-40"-27"	90	5"	35"
45SF37C	Super Flare-SFT	57	75"-41"-24"	150	6"	32"
45SF38C	Volume Flare-VFT	78	75"-41"-39"	175	6"	47"

- Designed for easy loading and unloading
- Ideal as an extractor truck
- Top Flange for additional strength
- Polyethylene, Corrosion Free – RotoBase
- Non-Marking Wheels
- Nominal Wall Thickness .225
- Nestable



Roto Utility Truck



Item#	Description	Capacity CU.FT.	Truck OD L-W-H	Unit Wt. (Lbs.)	Caster Size	Assembly Ht.
45RU17	RUT	19	42"-28"-28"	85	5"	36"

- Straight side walls
- Molded-in horizontal ribs for greater strength
- Strong, Durable Flanged Top
- Nominal wall thickness .280
- Polyethylene, Corrosion Free – RotoBase
- Non-Marking Wheels
- Nestable