

# Rotonics Cone Bottom Tanks

[www.rotonics.com/tanks/RMII/Cone.htm](http://www.rotonics.com/tanks/RMII/Cone.htm)

## RMII-1

- Available in Crosslink Polyethylene or FDA approved High Density Linear Polyethylene (ANSI/NSF Standard 61).
- These heavy duty tanks are used for mixing, settling, and storage of dry materials, as well as highly viscous solutions, up to 16.5 lbs./gallon.
- Basic stands are equipped with forklift channels.
- Seamless, one piece construction.

- Installed inlets and outlets are available to fit certain specifications.
- Impact and corrosion resistant.
- Optional mixer mounts and pump platforms are available.
- Ball valves and quick-release disconnects are available for the Cyclone.
- Cyclone has a dish bottom design for complete drainage and accepts 2" or smaller tank adapters.



### Open Top

Item#	Size (Gal.)	Dia. (In.)	Ht. (In.)	Ht. w/Stand (In.)	Degree of Slope
6501	920	90	63	76	50
6506	1440	90	79	92	50
6511	2175	90	106	119	50
6516	2900	90	136	149	50

### Dome Top

Item#	Size (Gal.)	Dia. (In.)	Ht. w/Lid (In.)	Ht. w/Stand (In.)	Lid (In.)	Degree of Slope
6635	15	20	21		16	60
6630	30	30	31		16	60
6475	55	32	33	53	8/16*	60
6485	115	32	50	70	8/16*	60
6490	175	32	68	88	8/16*	60
6495	230	32	85	105	8/16*	60
6496	500	52	82	102	24	60
6497	700	52	110	130	24	60
6500**	1100	90	77	90	16	50
6505**	1600	90	96	109	16	50
6510**	2300	90	123	136	16	50
6515**	3000	90	149	162	16	50

\*Larger Lid Optional

\*\*Molded-in lifting lugs available upon request.

### All Polly Cyclone Cone Bottom

[www.rotonics.com/tanks/RMII/Cyclone.htm](http://www.rotonics.com/tanks/RMII/Cyclone.htm)

Item#	Size (Gal.)	Dia. (In.)	Height (In.)	Overall Ht. w/lid Base (In.)	Lid (In.)
364981	525	56	35	80	16
36498	780	56	35	104	16
6499	*Poly Base	56	35		

\*All Poly Tank Base standard color is black

Limited Tank Warranty: RMI warrants to the original purchaser all tanks manufactured by RMI to be free from defects in material and workmanship for a period of five (5) years from date of manufacture, with the exception of D.O.T. and Septic Tanks, which have a special warranty. The Guido Tanks also have a (5) year warranty. Review the chemical resistance guide and warranty instruction information prior to the installation and use of RMI Tanks. Hard-plumbing of tanks is not recommended due to the expansive/contractive characteristics of Polyethylene. All weights, dimensions, and gallowage markers are approximate.

Rotonics Manufacturing Inc.  
716 North 11th Avenue • Caldwell, ID 83605  
Phone: (208) 454-9271 • Fax: (208) 454-3089  
E-mail: [idaho@rotonics.com](mailto:idaho@rotonics.com)  
[www.rotonics.com](http://www.rotonics.com)

# Rotonics Liquid Transporter Tanks

[www.rotonics.com/tanks/RMII/allpolyliquidtransporter.htm](http://www.rotonics.com/tanks/RMII/allpolyliquidtransporter.htm)

## RMI-I

- Crosslink Polyethylene Liquid Transporter Tanks offer tremendous chemical resistance.
- Tanks are available with sturdy four-way forklift skid for easy loading and handling.
- 7" or 16" threaded fill cap for easy access and cleaning.
- Sump bottom for maximum drainage with a protected 2" valve.
- Natural polyethylene allows for liquid level viewing.
- Units with skids are capable of stacking two high and two across in a standard truck.

- Molded from FDA approved High Density Polyethylene for use in the cosmetic and food industries.
- Durable tank with double molded pallet suitable for mixing, storage, and shipping of a variety of liquids.
- 10" threaded filler cap for easy clean out.
- Protected 2" recessed valve allows drainage from the lowest level of the tank for complete product discharge.
- Available in Crosslink Polyethylene for optimum chemical resistance.



“All Poly” Tote

Item#	Size (Gal.)	Ht. w/Lid (In.)	Width (In.)	Length (In.)	Lid (In.)
6309	275	40	48	42	8



“All Poly” Liquid Transporter

Item#	Size (Gal.)	Dia. (In.)	Ht. w/Lid (In.)	Lid (In.)
6316	300	47	60	10

Limited Tank Warranty: RMI warrants to the original purchaser all tanks manufactured by RMI to be free from defects in material and workmanship for a period of five (5) years from date of manufacture, with the exception of D.O.T. and Septic Tanks, which have a special warranty. The Guido Tanks also have a (5) year warranty. Review the chemical resistance guide and warranty instruction information prior to the installation and use of RMI Tanks. Hard-plumbing of tanks is not recommended due to the expansive/contractive characteristics of Polyethylene. All weights, dimensions, and gallonage markers are approximate.

Rotonics Manufacturing Inc.  
 716 North 11th Avenue • Caldwell, ID 83605  
 Phone: (208) 454-9271 • Fax: (208) 454-3089  
 E-mail: [idaho@rotonics.com](mailto:idaho@rotonics.com)  
[www.rotonics.com](http://www.rotonics.com)