

Rotonics Sherman Double Wall Tanks



- Available in Crosslink Polyethylene or FDA approved High Density Linear Polyethylene (ANSI/NSF Standard 61).
- Primary tank nests securely into Containment Basin for spill protection.
- Enclosed design prevents debris, rain, etc. from collecting in basin, while still providing containment.
- Top surface of tank has designated locations to accommodate meters and pumps.
- Available in natural or other colors upon request.
- Impact and corrosion resistant.
- Seamless, one piece construction.



Sherman Double Wall Tanks

www.rotonics.com/tanks/RMI/Sherman.htm

Item#	Size (Gal.)	Dia. (In.)	Height (In.)	Total Ht. w/Lid (In.)	Lid (In.)
6313	18 Gal. Vertical Tank with		21		
63131	21 Gal. Overflow Basin	23	19	23	8
6317	35 Gal. Vertical Tank with		34		
63171	46 Gal. Overflow Basin	23	31	35	8
6319	65 Gal. Vertical Tank with		36		
63191	77 Gal. Overflow Basin	28	32	37	8
6321	120 Gal. Vertical Tank with		44		
63211	140 Gal. Overflow Basin	33	40	44	8



Limited Tank Warranty: RMI warrants to the original purchaser all tanks manufactured by RMI to be free from defects in material and workmanship for a period of five (5) years from date of manufacture, with the exception of D.O.T. and Septic Tanks, which have a special warranty. The Guido Tanks also have a (5) year warranty. Review the chemical resistance guide and warranty instruction information prior to the installation and use of RMI Tanks. Hard-plumbing of tanks is not recommended due to the expansive/contractive characteristics of Polyethylene. All weights, dimensions, and gallonage markers are approximate.

Rotonics Manufacturing Inc.
 716 North 11th Avenue • Caldwell, ID 83605
 Phone: (208) 454-9271 • Fax: (208) 454-3089
 E-mail: idaho@rotonics.com
www.rotonics.com